





JTDZ-1000 Glass CNC Machining Center

Product descriptions and features

Features

- Natural granite machine bed, high precision, good anti-corrosion
- It can be programmed in CNC controller or programmed by computer
- Precision parts have dustproof fittings for good dustproof protection
- Automatic workpiece loading and unloading, reduce labor cost and increase production efficiency

For Material

Glass, ceramic, acrylic, non-metal oxide microchip

Applied Range

Machining of glass of consumer electronics, acrylic, ceramic





KEJIE website

KEJIE wecha



Parameters

Item	Parameter
Working area X/Y/Z	500/500/150/150mm
Work table size	1000×500mm
Max load of table	100kg
Spindle power Max spindle speed	2.5kw/40000rpm
Rapid traverse rate	20m/min
Cutting feed rate	15m/min
Positioning accuracy	0.008mm
Repeatability	0.005mm
Weight	3500kg
Machine dimension	1900×1880×2300mm
Powersupply	3-PH AC380V ±5% 50Hz

Standard Accessories

- JIATIE high speed CNC controller
- High speed spindle (Double Z axes)
- AC servo motor
- Precision ball screw and guide rail
- Hand Wheel
- Spindle cooling system

Optional Accessories

- Automatic robot manipulator for loading and unloading of workpiece
- Voltage stabilizer
- Oil mist collector (for machine with full protective hood)
- Cutting fluid filter
- Automatic tool changer with large capacity





